

3587 SUPER GRES P FAST

THIXOTROPIC EPOXY MASTIC FOR GRANITE, MARBLE, STONE AND PORCELAIN STONEWARE



Building



By spatula



Two-component



Dry sandable

Description and Use

Fast epoxy mastic for application to vertical surfaces, featuring strong adhesion properties and good weathering resistance. Especially suitable for works on granite, marble, stone and porcelain stoneware.

Substrate preparation

Surfaces to be treated must be perfectly dry, clean, dust free, without grease or wax traces. For any further information, apply to our TECHNICAL SERVICE.

Application

Application method:

- trowel

Product preparation:

Stir thoroughly the two components according to the recommended ratio, up to get an homogeneous mass.

Application method:

Apply having care to spread well the filler on the surface, making a light pressure on the spatula.

It is suggested 200÷250 gr per each catalyse.

The complete hardening and the maximum chemical resistance will be reached after 7 days.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life in months specified in the table of products with expiry date. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with the current legislation.

Table of products with expiry date

Product name	Code	Expiry date in months
SUPER GRES P FAST A	3587	24
SUPER GRES P FAST B	4587	12

Technical features

Colour	white, cream, black
Binder	epoxy-polyamine
Specific gravity comp. A	1.6 kg/l (± 0.02)
Specific gravity comp. B	1.8 kg/l (± 0.02)
Curing ratio	2:1 weight of A /weight of B
Component B	code 45870000
Gel time	10-15 minutes
Workable	after 1 hour
The data are measured at a temperature of 20°C and 65% R.H.	

Warnings

- For professional use only.
- Use outside the scope of the UNI EN 12004 standard.
- Always read the safety datasheet before use.
- Solvents or thinners used for cleaning tools, as well as any product residues, must not be released into the environment or poured down domestic drains. The recipient/product/thinner or cleaning solvent must be disposed of in accordance with national regulations.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

Do not use the product when the temperature is below + 10°C (50°F) and the R.H. exceeds 80%, because the reaction becomes too slow.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.