

1258 ANTIROMBO A PENNELLO

UNDERBODY PROTECTION



Car refinish



Brush



Ready-to-use



See warnings

Description and Use

Protective coating based on oxidized bitumen and inert lamellar extenders.

The product is suitable for use in industrial body shop work as soundproofing compound for underside of fenders, industrial truck bottoms, car chassis, refuse containers, doors and windows metal fittings, etc.

It can be also applied on underground tank and pipes.

Substrate preparation

Surfaces must be dry, clean, dust free and made slightly rough by sanding.

Product can be applied directly on bare steel sheet or over a primer.

Application

Application method:

- Brush

The product is ready to use. In case of necessity can be diluted with DILUENTE NITRO cod. 1616

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 12 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with the current legislation.

Technical features

Colour	black
Binder	bituminous
Appearance of the dry film	satin
Total non-volatile by weight	79% (± 1)
Specific weight	1.40 kg/l (± 0.02)
Viscosity	40000-50000 mPa.s Brookfield rpm 10 s 6
Recommended thicknesses	300 μ m wet equivalent to 250 μ m dry
Indicative actual yield	2-3 m ² /kg
Air drying (20°C - 65% RH)	1 hour. dust-free
	24 hours, through drying
Recoatible	not overcoatible
EU limit values for VOC content (Directive 2004/42/EC)	Category B/e, SB: VOC max 840g/l product VOC < 840g/l
The data are measured at a temperature of 20°C.	

Warnings

- **The product contains synthetic polymer microparticles (SPM).**
- **INSTRUCTIONS TO PREVENT THE RELEASE OF SYNTHETIC POLYMER MICROPARTICLES INTO THE ENVIRONMENT**
- **In accordance with Regulation (EU) 2023/2055, please follow the procedures below to prevent environmental release.**
- During use and application, avoid accidental release of the product onto soil, into drains, or household wastewater. Apply the product only to the surfaces to be treated.
- Any remaining product should be stored by tightly sealing the original container. Dispose of the product/container in accordance with national regulations.
- If you wish to reuse the tools used for application, follow these steps to clean them in an environmentally responsible manner.
- The water, solvents or thinners used for cleaning tools, as well as any product residues, **MUST NOT** be released into the environment or poured down domestic drains.
- Remove as much product as possible from the tools used.
- Soak the tools in hot water or in solvent for at least a couple of hours, then remove them from the container.
- Allow the water in the bucket to evaporate and let the tools dry. For solvent-based products, close the container. Do not release the product into the environment and do not pour it into drains.
- Deliver the container with any remaining product / wash water / solvent / cleaning thinner to an authorised waste collection centre, in accordance with national regulations.
- For professional use only.
- Always read the safety datasheet before use.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

High ambient humidity and excessive thickness may delay hardening of the applied film.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.