

2006 VERNICE TRASPARENTE SPRAY

ONE-PACK GLOSSY ACRYLIC VARNISH



Car refinish



Ready-to-use



Shake before use

Description and Use

One-component clear varnish based on acrylic resins, characterized by fast drying, suitable for repairing, retouching and maintenance of internal parts of vehicles in car refinish.

Substrate preparation

Surfaces to be treated must be dry, clean and contaminants free.

Application

Application method:

- Spray at 25-30 cm from surface.

Product preparation:

Shake well the can for 2 minutes before using it.

Recommended thicknesses:

20-30 dry μm , applying several thin layers.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 12 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with the current legislation.

Technical features

Colour	transparent
Appearance of the dry film	glossy
Binder	acrylic resins
Practical cover rate *	1.25-2.0 m^2 per one spray can
Air drying	6 hours, through drying
EU limit value of VOC content (Directive 2004/42/EC)	Category B/e, SB: VOC max 840g/l product VOC < 840g/l
* The cover rate is calculated on the suggested thickness and applied on plane and regular surfaces.	
The data are measured at a temperature of 20°C and 65% R.H.	

Warnings

- For professional use only.
- Always refer to the safety data sheet for the relevant products.
- Solvents or thinners used for cleaning tools, as well as any product residues, must not be released into the environment or poured down domestic drains. The recipient/product/thinner or cleaning solvent must be disposed of in accordance with national regulations.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.